

## COMPARISON WITH OTHER PANELS

- ▶ rainproof and shock resistant aluminum body
- ▶ 100% silent fan-free operation
- ▶ 2 times more light output
- ▶ much longer through (up to 1600 lux at 6m)
- ▶ more than bi-colour 2700K to 6500K
- ▶ digital display with shock resistant buttons
- ▶ perfect color rendition & consistency lamp to lamp
- ▶ professional DMX RDM with XLR-5 connector
- ▶ wide power input 12-35 VDC / 90-264 VAC
- ▶ affordable European quality
- ▶ 2 years warranty 100% made & designed in Barcelona (Spain)



[www.thelight.com.es](http://www.thelight.com.es)

[info@thelight.com.es](mailto:info@thelight.com.es)

Intellectual Property

THELIGHT VELVET light technology is protected under  
spanish patents and international patents pending

2015 © Copyright THELIGHT. All rights reserved.

## the beaming rainproof 1x1 LED panel

**VELVET** 1  
POWER



**RAINPROOF**

Rocky body 100% aluminum

**SILENT**

Fan-free operation

**POWERFUL**

2000 Lux at 3m / 10 ft

**THELIGHT**  
the unique aLL-in-one Light



THELIGHT introduces **Rainproof VELVET Power 1** the most robust and advanced LED panel producing long throw light without noisy fans



### MADE TO LAST

#### Rainproof IP54

Robust 100% aluminum body made to endure the tougher working conditions on any location or studio

#### Silent operation

THELIGHT state of the art passive cooling technology keep LED in their optimum temperature to last beyond 50.000 hours without fans to be serviced

### ADVANTAGES

- ▶ Rainproof and shock resistant aluminum body
- ▶ More than bi-colour 2700K to 6500K
- ▶ Maintenance free without fans
- ▶ Long throw beam light
- ▶ High output 800 Lux at 10 meters
- ▶ Worldwide AC & DC powered
- ▶ On-board and DMX control
- ▶ Thin and portable
- ▶ Modular design for multipanel
- ▶ Flicker free up to 3000 fps
- ▶ Silent fan-free operation
- ▶ 100% Made in Barcelona (Spain)



### VELVET Power 1 includes:

- ▶ 100% aluminum IP54 rainproof LED panel
- ▶ On-board and DMX digital control over:
  - ▶ Color temperature from 2700K to 6500K
  - ▶ smooth Flicker-free dimming 0 to 100
- ▶ XLR-3 input for battery power 12-35VDC
- ▶ XLR-5 input connector for remote DMX control
- ▶ adjustable yoke with combined 28 / 16mm pin
- ▶ two years warranty

### LONG THROW BEAM

Incredibly powerful 15° or 30° beam of light to be used up to 15 meters distance  
The light can be easily shaped and soften with the choice of magnetic attach diffusers

### MORE THAN BI-COLOR

VELVET Power 1 is more than tungsten & daylight in the same unit: you can adjust color temperature from 2700K to 6500K

### AC/DC POWERED

VELVET is always ready to operate worldwide: using any battery from 12 to 35 VDC with **Vlock or Gold battery mount** with universal AC power 90-264 VAC

### VELVET QUALITY WHITE LIGHT

CRI >90 to get perfect skin tones and real colors with any HD or photo camera

#### Professional and consistent color rendition

Absolutely consistent lamp to lamp to mix with any VELVET panel and get the same high quality and color reproduction

### QUICK SETUP

On-board control, digital display and **shock resistant buttons** color temperature **instantly adjustable** from 2700K to 6500K dimmer smooth and flicker-free 0 to 100 with no color shift

### ADVANCED DMX RDM

bi-directional DMX remote control even without a controller!  
**Master-slave function:** to operate without console

## TECHNICAL SPECIFICATIONS

### VELVET Power 1 Flood

### VELVET Power 1 Spot

COLOR TEMPERATURE	digitally adjustable from 2700K to 6500K	
LIGHT INTENSITY	dimnable 0 to 100 (smooth and flicker-free)	
DIMENSIONS	385 x 308 x 68 mm	
WEIGHT	4,5 Kg	
POWER DRAW	100W (7 Amps at 14,4 VDC - 0,44 Amps at 230VAC)	
POWER SUPPLY	12-35V DC via XLR-3 14,4V DC Vlock or Gold mount battery plate 90-264V AC 50/60Hz	
PHOTOMETRICS	18.000 Lux / 1.660 fc at 1m / 3 feet 2.000 Lux / 185 fc at 3m / 10 feet 650 Lux / 60 fc at 6m / 20 feet	38.000 Lux / 3.520 fc at 1m / 3 feet 6.000 Lux / 556 fc at 3m / 10 feet 1.600 Lux / 148 fc at 6m / 20 feet
BEAM ANGLE	30° tunable with optic diffusers	15°
LED RATED LIFE	more than 50.000 hours	
COOLING	no noise, fan-free passive cooling	
PROTECTION & CONSTRUCTION	rainproof IP54 rated, made of black anodized extruded aluminum and black powder coated sheet aluminum	
VELVET LED TECHNOLOGY	selected BIN High-power LED + THELIGHT custom optics + CPU software control	
QUICK MOUNTING ACCESSORIES	AC power supply, Vlock or Gold adapter, magnetic attach diffusers, pole-op yoke, multipanel yokes, removable barn doors, DMX splitter cable, hard case, Cordura soft case	



Specifications subjects to change without notice